





## HOLLEY® FUEL SYSTEM SELECTION CHART

Part Number	Application	Fuel Compatibility	Compatible up to 18.5V	GPH Flow at Rated PSI and 13.5V	Holley Recommendations for Peak Performance										Holley Recommendations for Peak Performance						Max Amp Draw	
					Max HP*		Pump Fitting Size		Minimum Recommended Line Size			Fuel Filter (Carbureted)		Fuel Filter (Fuel injected)		Recommended Regulator						
					Naturally Aspirated	Forced Induction	Inlet	Outlet	Inlet	Outlet	Return	Pre	Post	Pre	Post	Carb	EFI					
The pumps below do not have an internal bypass. A bypass style regulator and return line are required.																						
	12-700	Street/Strip	Gasoline / Diesel	Yes	75 @ 8 PSI 57 @ 43 PSI 47 @ 60 PSI	900 700 550	690 530 430	-8AN	-8AN				-6 AN	-6AN	-6AN	162-564	162-555	162-564	162-554	12-845	12-846	13 Amps
	12-890	Street/Race	Gasoline / Diesel	Yes	96 @ 8 PSI 76 @ 43 PSI 70 @ 60 PSI	1050 900 800	800 700 600	-8AN	-8AN				-8AN	-6AN	-6AN	162-564	162-555	162-564	162-554	12-845	12-846	18 Amps
	12-1400	Street/Race	Gasoline / Diesel	Yes	155 @ 8 PSI 122 @ 43 PSI 105 @ 60 PSI	1830 1400 1250	1425 1125 975	-10AN	-10AN				-10AN	-8AN	-8AN	162-572	162-571	162-572	162-570	12-847	12-848	23 Amps
	12-1800	Race	Gasoline / Diesel	Yes	190 @ 8 PSI 156 @ 43 PSI 140 @ 60 PSI	2100 1800 1600	1600 1400 1200	-10AN	-10AN				-10AN	-10AN	-10AN	162-572	162-571	162-572	162-570	12-847	12-848	36 Amps

\*Horsepower estimates are based on gasoline. Individual systems will vary based on fuel system design, regulator type, fuel cell location, launch G's etc.

